


| | | |
|--------------------------|--|---|
| DESCRIPTION | 8 and 11 Pin Square Base Sockets | |
| ELECTRICAL RATING | <ul style="list-style-type: none"> • 300 Volts, 10 Amps • 150 Volts, 15 Amps | |
| CONSTRUCTION | Contacts • Brass, Nickel Plated Screws • Binder Head, 6 - 32 x 1/4" Steel, Zinc Plated • Pressure Clamp, 6 - 32 x 5/16" Steel, Zinc Plated, Wire Range #12 - #22 Solid or Stranded Molding • Break Resistant Thermoplastic | |
| AGENCY APPROVALS | <ul style="list-style-type: none"> • UL recognized, File No. E60008 • CSA certified, File No. LR29513 • CE |  |

SS SERIES

RELAY SOCKETS



| ORDERING CODE | | |
|---------------|---------------------|-----------------------|
| PART NO. | DESCRIPTION | TERMINAL TYPE |
| SS08 | DPDT, 8 Pin Square | Binder Head Screws |
| SS08-PC | DPDT, 8 Pin Square | Pressure Clamp Screws |
| SS11 | 3PDT, 11 Pin Square | Binder Head Screws |
| SS11-PC | 3PDT, 11 Pin Square | Pressure Clamp Screws |

| ACCESSORIES | DESCRIPTION |
|-------------|--|
| PART NO. | (Refer to the accessories pages 25-27) |
| HDB-8 | Hold Down Spring |

