










Wanjia Relay 持繼電器系列

MAGNETIC LATCH RELAYS

產品型號 Model		WJ315	WJ316	
外觀 Appearance				
外型尺寸 Dimension(mm)		29.0 × 12.5 × 25.0	100.0 × 79.5 × 30.0	
觸點形式 Contact Arrangement		1C, 2C	2A	
觸點容量 Contact Capacity		200 100 80 60 40 20	200A  16A 5A 	
最大切換電壓 MAX Switching Voltage VDC/VAC		30VDC/250VAC	30VDC/250VAC	
最大切換功率 MAX Switching Power W/VA		480W/4KVA	50KVA	
線圈參數 Coil Data	額定電壓 Nominal Voltage DC	5 ~ 48VDC	5 ~ 48VDC	
	斷開電壓 Make-Break Voltage	≤ 70%	≤ 75%	
	反向斷開電壓 Contact Make-Break Voltag	≤ 70%	≤ 75%	
	脈衝寬度 Pulse Width (ms)	≥ 30ms	≥ 30ms	
	功 耗 Coil Power W	1W	(S)單:12W, (D)雙:24W	
性能參數 Specifications Data	接觸電阻 Contacts Resistance (mΩ)	≤ 15mΩ	≤ 2mΩ	
	絕緣電阻 Insulation Resistance (MΩ)	≥ 1000MΩ	≥ 1000MΩ	
	介質耐壓 Dielectric Strength Vr. m. s	觸點間 Between Open Contacts	≥ 1000VAC	≥ 4000VAC
		觸點線圈 Between Coil & Contacts	≥ 3000VAC	≥ 4000VAC
		觸點組間 Between Contacts Form		
	環境溫度 Ambient Temp. (°C)	-40 ~ +50°C	-40 ~ +50°C	
	動作/釋放時間 Operation/Release Time(ms)	≤ 30/30ms	≤ 30/30ms	
電氣壽命 Service Life	電氣 Electrical (Operation)	5 × 10 ⁴	1 × 10 ⁴	
	機械 Mechanical (Operation)	1 × 10 ⁶	1 × 10 ⁶	
安裝開孔尺寸 Mounting Holes(mm)				
安裝形式 Mounting Method		P. C. B.	Welding	
重 量 Weight(gr)		18.0	330.0	
安全標準 Safety Approval				
參考型號 Model Cross Reference			GRUNER: 740 KG200	