



Feature -

small dimension  
max. 8 positions


Application -

high value toy  
power strip voltage selector  
selection key on the application  
AV machine, video recorder, air cleaner

► SPECIFICATIONS


SWITCH SPECIFICATIONS	
POLE - POSITION	1POLE , 2 POSITION~8 POSITION ( STOP LESS ) are Available
CONTACT RATING	0.5A 24V DC ; 0.2A 48V DC
CONTACT RESISTANCE	2 Ω MAX. 1.5 V DC ; 100 mA , by Method of Voltage DROP
INSULATION RESISTANCE	100 MΩ MIN. 500 V DC
DIELECTRIC STRENGTH	Breakdown is not Allowable ; 500 V AC for 1 Minute
OPERATING FORCE	400 ± 250 gf.cm 230 ± 100 gf.cm
OPERATING LIFE	2,000 cycles
OPERATING TEMPERATURE RANGE	-40°C ~ 85°C

► HOW TO ORDER




▶ DIMENSION

MR - 18 - A8




▶ OTHER ACTUATOR TYPE


A TYPE




B TYPE



C TYPE




D TYPE




▶ KNOB OPTION

A TYPE




B TYPE




▶ CIRCUIT

TRAVEL	SWITCHING POSITION
0°	C - C (OFF)
45°	C - 1
90°	C - 2
135°	C - 3
180°	C - 4
225°	C - 5
270°	C - 6
315°	C - 7



▶ P.C.B. LAYOUT



▶ MATERIAL

- FRAME : PA + GF
- SHAFT : PA + GF
- TERMINAL :  
BRASS GOLD PLATING